

# ZyPer4K-XSE

Product Number: Z4KC2XS-EAU



## Uncompressed 4K Encoder with Dante and Icron USB

Z4KC2XS-EAU is an HDMI 2.0 Encoder that is part of the ZyPer4K product line. It supports IP streaming over 10Gbit copper PoE+ up to 4KP60 4:4:4 resolution with embedded Dante audio support and HDCP 2.3 encryption at zero-frame latency. Configurable Icron USB allows support between any USB enabled ZyPer4K device. Video compatible with any ZyPer4K Decoder. AC power supply is included but other cables are not.

### Z4KC2XS-EAU



Audio In/Out  
port



10Gb  
Ethernet  
port



1 Gb  
Utility  
port



HDMI  
Output



HDMI  
Input



USB-C  
ports

## What's in the box?

- ZyPer4K-XSE Encoder Copper
- Power Supply



ZyPer4K-XSE Encoder	Information	
Video Input	HDMI 2.0 with HDCP pass-through and USB-C with DP Alt Mode 1.3 Support	
Video Output	HDMI 2.0 (loop-out of active video input)	
USB-C Charging Input	Input USB-C power to support charging on USB-C Input port to 60W	
Audio (Digital)	Encoded audio formats and linear PCM up to 8 channels	
Audio (Analog)	Balanced Stereo (Input/Output)	
USB	USB 2.0 (USB-C connector) Note: Full USB 2.0 Support via Icron chipset	
Ethernet	10 Gb for Video/Audio/Control with 1 Gb Utility	
Other Specifications	ZyPer4K-XSE Encoder	
Formats	Supports all major VESA resolutions and variations including full HDMI 2.0 support: VGA: 640x480 (4:3) XGA: 1024x768 (4:3) SXGA: 1280x1024 (5:4) SXGA+: 1440x1080 (4:3) 1080p/i: 1920x1080 (16:9) Ultra HD: 3840x2160 (16:9) SVGA: 800x600 (4:3) HDTV: 1280x720 (16:9) WXGA: 1366x768 (16:9) UXGA: 1600x1200 (4:3) QXGA: 2048x1536 (4:3) 4K: 4096x2160 (17:9)	
	Custom resolutions are supported at pixel clock rates up to 600 MHz	
	Video Other	
	Color depth: 24 bit, 30 bit, 36 bit, 48 bit	
	Video Wall and Multiview	
	Video Wall up to 15x15. Multiview with up to 19 sources	
	Signal transmission distance	
	Cat6a: 100m	
	Copy Protection/Security	
HDCP 2.3, AES-128 Encryption, 802.1X compatible		
Power input (locking connector)	12V DC	
Power	Approximately 13 watts	
Dimensions (L x W x H) / Weight	7.8 in (199mm) x 5.4 in (136mm) x 1.9 in (48mm), 35.2 oz (1000g)	
Temperature	Operating temperature: 32 F to 104 F <0 C to +40 C> Storage temperature: -4 F to +176 F <-20 C to +80 C>	
Humidity	Operating/ Storage: 20% to 90% (Non-Condensing)	
Accessories	Description	
Z4KPWRCTR12	ZyPer 12V Power Center for use with up to 8 ZyPer Encoder/Decoders (all models). 1 RU. Includes rack ears, 8 3-foot locking 12V DC power cables, AC power cord.	
Z4KRACKXSE	ZyPer4K-XSE Rack Mount Kit. Holds up to 8 ZyPer4K-XSE Encoders/Decoders in standard 6RU space. Includes rack assembly and 8 carrier units	
Z4KVESABRK	ZyPer4K VESA Bracket is a custom wall/desk/display mount bracket for ZyPer4K. Supports standard VESA parameters for mounting directly to rear of a display. 100x100, 100x200 and 200x200 VESA hole mounts are supported.	

#### ENTIRE PRODUCT LINE:

Z4KDECC3XS	Z4KC2XS-E	Z4KC2XS-D
Z4KDECF3XS	Z4KC2XS-EAU	Z4KC2XS-DAU
Z4KENCC3XS	Z4KF2XS-E	Z4KF2XS-D
Z4KENCF3XS	Z4KF2XS-EAU	Z4KF2XS-DAU

#### ZYPER4K-XS WALL PLATES:

Z4KENCC3XS-WPUS-I
-------------------