

ZyPer4K-XSE

Product Number: Z4KF2XS-D



Uncompressed 4K Decoder

Z4KF2XS-D is an HDMI 2.0 Decoder that is part of the ZyPer4K product line. It supports IP streaming over 10Gbit/fiber up to 4K60 4:4:4 resolution with embedded audio and HDCP 2.3 encryption at zero-frame latency. USB supported between ZyPer4K-XS/XR devices. Video compatible with any ZyPer4K Encoder. AC power supply is included but other cables are not.

Z4KF2XS-D



Audio Out port



10Gb Ethernet port

1 Gb Utility port

USB ports

Serial (RS232) HDMI 2.0 Output

What's in the box?

- ZyPer4K-XSE Decoder Fiber
- Power Supply

ZyPer4K-XSE

Product Number: Z4KF2XS-D



ZyPer4K-XSE Decoder		Information
Video	HDMI 2.0 with HDCP pass-through	
Audio (Digital)	Encoded audio formats and linear PCM up to 8 channels	
Audio (Analog)	Balanced Stereo (5-pin phoenix) Output	
Serial (RS232)	3-pin phoenix	
USB	Dual USB 2.0 (USB - A connectors) Note: HID Support Only	
Ethernet	10 Gb for Video/Audio/Control with 1 Gb Utility	
Other Specifications		ZyPer4K-XSE Decoder
Formats	Supports all major VESA resolutions and variations including full HDMI 2.0 support:	
	VGA: 640x480 (4:3)	XGA: 1024x768 (4:3)
	SXGA: 1280x1024 (5:4)	SXGA+: 1440x1080 (4:3)
	1080p/i: 1920x1080 (16:9)	Ultra HD: 3840x2160 (16:9)
	SVGA: 800x600 (4:3)	HDTV: 1280x720 (16:9)
	WXGA: 1366x768 (16:9)	UXGA: 1600x1200 (4:3)
	QXGA: 2048x1536 (4:3)	4K: 4096x2160 (17:9)
	Custom resolutions are supported at pixel clock rates up to 600 MHz	
	Video Other	
Video depth: 24 bit, 30 bit, 36 bit, 48 bit		
Video Wall and Multiview		Video Wall up to 15x15. Multiview with up to 19 sources
Signal transmission distance		Multimode Fiber: 300m, Single Mode Fiber: 10km
Copy Protection/Security		HDCP 2.3, AES-128 Encryption, 802.1X compatible
Power input (locking connector)		12V DC
Power		Approximately 13 watts
Dimensions (L x W x H) / Weight		7.8 in (199mm) x 5.4 in (136mm) x 1.9 in (48mm), 35.2 oz (1000g)
Temperature		Operating temperature: 32 F to 104 F <0 C to +40 C> Storage temperature: -4 F to +176 F <-20 C to +80 C>
Humidity		Operating/ Storage: 20% to 90% (Non-Condensing)
Accessories		Description
Z4KPWRCTR12		ZyPer 12V Power Center for use with up to 8 ZyPer Encoder/Decoders (all models). 1 RU. Includes rack ears, 8 3-foot locking 12V DC power cables, AC power cord.
Z4KRACKXSE		ZyPer4K-XS Rack Mount Kit. Holds up to 8 ZyPer4K-XS Encoders/Decoders in standard 6RU space. Includes rack assembly and 8 carrier units
Z4KVESABRK		ZyPer4K VESA Bracket is a custom wall/desk/display mount bracket for ZyPer4K. Supports standard VESA parameters for mounting directly to rear of a display. 100x100, 100x200 and 200x200 VESA hole mounts are supported.

ENTIRE PRODUCT LINE:

Z4

KDECC3XS
DECODER

Z4KC2XS-E

ENCODER

Z4KC2XS-D

DECODER

Z4KENCC3XS-WPUS-I

KENCC3XS
RACK MOUNT

Z4KF2XS-E
Z4KF2XS-EAU

ENCODER

Z4KF2XS-D
Z4KF2XS-DAU

DECODER

ZYPER4K-XS WALL PLATES:

REGULATORY: IEC 62368-1 / IEC 60945 (Clauses 9 & 10) / IEC 61000 / EN55032 / EN55035: / FCC Part 15B / CE / CB