



## Galil 8-C

8Inch, 2Way ClosedBack Ceiling Speakers

| Speakers



The Galil 8C Closedback Ceiling Speaker features a multitap power transformer for selecting 8 (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation

### FEATURES

Type - 2way coaxial speaker

Woofer - 8" polypropylene cone

Tweeter - 1" silk dome

Impedance - 8

Power Handling - 64W RMS, 180W continuous program

Transformer Taps - 70V: 64W/32W/16W/8W/4W/Off (LoZ); 100V: 64W/32W/16W/8W/Off (LoZ)

UL 1480 & 2043 Listed

Package Includes - 2 speakers (1 pair), ceiling mounting kit, template and user manual



# KRAMER

## TECHNICAL SPECIFICATIONS

---

|                             |   |
|-----------------------------|---|
| DESCRIPTION:                | 2way closedback ceiling speakers  |
| FREQUENCY RESPONSE:         | 65Hz to 20kHz @10dB, 85Hz to 20kHz @±3dB                                  |
| WOOFER:                     | 8" (200mm) polypropylene with rubber surround                             |
| TWEETER:                    | 1" (25.4mm) silk dome   |
| IMPEDANCE:                  | 8 (transformer tap in off position)                                       |
| TRANSFORMER TAPS:           | 70V – 64W/32W/16W/8W/4W/Off (LoZ), 100V – 64W/32W/16W/8W/Off (LoZ)        |
| SENSITIVITY:                | 89dB SPL, 1W@1m   |
| MAX SPL:                    | Continuous: 104dB, peak: 107dB  |
| POWER HANDLING:             | 64W RMS, 180W continuous program  |
| CROSSOVER FREQUENCY:        | 6.3kHz  |
| COVERAGE ANGLE:             | 110°  |
| DIRECTIVITY FACTOR (Q):     | 4.6 averaged 1kHz to 10kHz  |
| DIRECTIVITY INDEX (DI):     | 6.5dB averaged 1kHz to 10kHz  |
| INPUT CONNECTOR:            | Terminal block  |
| MATERIALS:                  | ABS bezel, aluminum grill, metal back can                                 |
| OPERATING TEMPERATURE:      | 0° to +40°C (32° to 104°F)  |
| STORAGE TEMPERATURE:        | 40° to +70°C (40° to 158°F)   |
| HUMIDITY:                   | 10% to 90%, RHL noncondensing   |
| WEIGHT PER SINGLE SPEAKER:  | 4.9kg (10.8lbs) approx  |
| SHIPPING WEIGHT (FOR PAIR): | 13.6kg (30lbs) approx   |
| INSTALLATION CLEARANCE:     | Mounting depth: 22.6cm (8.9")   |
| CUTOUT DIAMETER             | 27.3cm (10.75")   |
| ACCESSORIES:                | Installation bracket, safety cord attached to grill, ceiling mounting kit |
| COLOR:                      | White   |

