



RC-52N

6-Button Universal Room Controller



The RC-52N is a 6-button room controller for multimedia rooms. It controls audio/video components and other room facilities such as lights and screens.

FEATURES

- **6 Backlit & Label Capable Buttons.**
- **Macro Capability** - Executes multiple commands with a single press of a button.
- **Fast Installation** - Simple mechanical design provides easy and quick installation in wall boxes.
- **Internal Clock.**
- **USB Port** - For uploading configuration files and supplying DC power during configuration.
- **RS-232 Port** - Controls AV equipment such as projectors, flat screen displays, power amplifiers, switchers and scalars.
- **IR Out Port** - Additional control port for AV equipment.
- **IR Features** - Learns commands from IR remotes and functions as an IR repeater.
- **Lock-Out Feature** - Locks and unlocks to prevent tampering.
- **Dimensions** - 6.9cm x 3.14cm x 11.4cm (2.71" x 1.23" x 4.49") US; 8.6cm x 2.06cm x 8.6cm (3.39" x 0.81" x 3.39") and 8cm x 2.06cm x 8cm (3.15" x 0.81" x 3.15") EU W, D, H.
- **Note** - Available in white, black, gray and brushed aluminum.



RC-52N

TECHNICAL SPECIFICATIONS

INPUT:	1 IR receiver.
PORTS:	1 RS-232 on a terminal block connector; 1 IR OUT on a terminal block connector; 1 USB port.
POWER CONSUMPTION:	5V DC, 150mA.
DIMENSIONS:	6.9cm x 3.14cm x 11.4cm (2.71" x 1.23" x 4.49") US; 8.6cm x 2.06cm x 8.6cm (3.39" x 0.81" x 3.39") and 8cm x 2.06cm x 8cm (3.15" x 0.81" x 3.15") EU W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, screwdriver.
OPTIONS:	RK-121WP 19" rack adapter, RS-232 9-pin D-sub port to 3-pin terminal block connector cable (C-D9F/3PM-0.6).