

VS-21DT

2x1 4K60 4:2:0 HDCP 2.2 HDMI Auto Switcher over HDBaseT | HDMI | HDCP Compliant | HDBaseT | 4K/60 UHD (4:2:0) | HDCP 2.2 Compatible



VS21DT is a highperformance automatic switcher for 4K, HDBaseT, HDMI 1.4, HDCP 2.2 video signals. Offering priority and lastconnected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

FEATURES

Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)

Max. Resolution - 4K@60Hz (4:2:0)

HDMI 1.4 & HDCP 2.2 Compliant

Supports up to 40m reach at 4K@60Hz (4:2:0)

Kramer Equalization and re-Klocking Technology

HDTV Compatible

3D Pass-Though



TECHNICAL SPECIFICATIONS

2 HDMI On female HDMI connectors

1 HDBT On an RJ45 connector

Max. Data Rate 8.91Gbps (2.97Gbps per graphic channel)

Max. Resolution 4K@60Hz (4:2:0)

Standards Compliance HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 1.4

Controls DIPswitches for selecting switching mode (Priority/Last Connected), contact

closure connectors for remote control switches

Indicators Active input, switching mode (Priority/Last Connected) and ON

Source 5V DC

Consumption 1A

REGULATORY CERTIFICATION:

EMC EN 55032;IEC 609501(ed.2);IEC 609501(ed.2)am1;IEC 609501(ed.2)am2

Operating Temperature 0° to +40°C (32° to 104°F)

Storage Temperature 40° to +70°C (40° to 158°F)

PRODUCT DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING DIMENSION: 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT: 0.5kg (1.1lbs) approx

Humidity 10% to 90%, RHL noncondensing

Included 5V DC power adapter

Optional RK3T 19" rack adapter

