



TBUS-1-KWC

TBUS with Wireless Charging Spot



Kramer's TBUS-1-KWC is an enclosure of TBUS-1A with an integrated, surface mount, wireless charging spot flush-mounted on the TBUS bezel.

FEATURES

- Integrated Wireless Charging Spot - For mobile phones integrated in the TBUS.
- Flush Surface.
- Power Supply - Requires a supply voltage of 24V DC at 500mA.
- Current Input - 1A, IEEE 802.15.4 based RF channels.
- Power Output - 6 to 15W.
- Regulatory Compliance - PMA type 3 compliant, FCC Title 47, Part 18
EMC Emission – EN5502/CISPR22, FCC part 15B
Safety – EN60950-1, EN60950-1, UL60950-1, IEC 60950-1, RoHS, REACH.

TECHNICAL SPECIFICATIONS

POWER SOURCE:	International power sockets available from 110V to 240V AC.
FUSE RATING:	T 6.3A 250V .
POWER CONSUMPTION:	Charging spot: 5V DC, 1A.
SAFETY REGULATORY COMPLIANCE:	CE, FCC.
OPERATING TEMPERATURE RANGE:	0° to +40°C (32° to 104°F).
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing.
STORAGE TEMPERATURE RANGE:	-40° to +70°C (-40° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing.
DIMENSIONS:	22.1cm x 18.2cm x 13cm (8.17"x 5.88" x 5.13") W, D, H
WEIGHT:	Gross weight: 2.3kg (5.07lbs) approx. TBUS-1-KWC with table clamps: 1.75kg (3.6lbs) approx. Metal template: 0.125kg (0.28lbs) approx.
ACCESSORIES:	Power cord, six self-locking ties, metal template, 1 KWC-MUSB, 1 KWC-LTN (see separate specifications), power supply, power supply bracket.
OPTIONS:	Inner frames, passive wall plates and interfaces, power socket kits, power supply, bracket for power supply.

CONFIGURATIONS

TBUS-1-KWC(B)	TBUS with Wireless Charging Spot - Black
TBUS-1-KWC(BC)	TBUS with Wireless Charging Spot - Brushed Clear