

HDBaseT Solution

OPS HDBaseT Receiver (100013612), HDBaseT Transmitter (100013613)

OPS Slot-in Signal Distribution

NEC's HDBaseT Transmitter and OPS Receiver is a clever solution that combines the advantages of HDBaseT and the OPS Standard allowing uncompressed HD multimedia content transmission up to 100m through a single network cable.

OPS HDBaseT Receiver (SB-07BC)



HDBaseT Transmitter (KT-100TX1)



HDBaseT features the delivery of uncompressed Full HD digital video plus audio, 100BaseT Ethernet, and control signals through a single 100m LAN cable. The HDBaseT Transmitter (KT-100TX1) converts the input signal and provides the high quality signals using a network cable to the OPS HDBaseT Receiver (SB-07BC) unit that is embedded into the displaying device thanks to the OPS form factor. HDBaseT allows cable distances up to 100 meters while exceeding the known limitations with current cable technologies. HDBaseT technology is a single wire solution working Plug and play and uses well-known terminations that are easy to pull through walls over long distances or using existing network cables, reducing installation cost and maintenance cost.

The HDBaseT-Receiver module is also compatible with the majority of third party HDBaseT-Senders and therefore offers a wide range of use and high flexibility.



Delivering Genuine Benefits

No more cable length limitations: HDBaseT technology can be used over 100 m with a single hop and overcomes known cable limitations

One single cable only: HDBaseT delivers video, audio, Ethernet and controls over a single cable, enabling to reduce the cable assortment down to one single cable

Easy set-up and operation: Time saving installation using well known cable types and working Plug & Play saving installation cost

Wide range of applications: Ideally suited for Rental & Staging, Leisure & Museums, Corporate & Education and all other applications that need to cover long cable distances

Compact and fully embedded: All connectors are inside the displays including Ethernet, Video & Audio Signals and RS232. No External Cables Required

High Flexibility: Compatible with NEC Large Format Displays (featuring OPS or DualSlot) and also NEC PX Series and PH Series installation projectors

HDBaseT Solution



OPS HDBaseT Receiver (100013612), HDBaseT Transmitter (100013613)

TECHNICAL SPECIFICATIONS

	OPS HDBaseT RECEIVER	HDBaseT TRANSMITTER
GENERAL		
Manufacturing Code	SB-07BC	KT-100TX1
Order Code	100013612	100013613
RESOLUTION		
Video	480i, 576i, 480p, 576p, 1080i@50/60Hz, 720p@50Hz/60Hz, 1080p@24Hz/25Hz/50Hz/60Hz 640x480@60Hz to 1920x1200@60Hz(RB), 4K2K@24/25/30Hz	
Colorspace	RGB, YCbCr	
Color depth	8-bit	
AUDIO		
Formats	PCM 2 ch	
DISTANCE		
CAT5e/6	100 meters	
SIGNAL		
Bandwidth	10.2 Gbps	
HDCP	Yes	
CONTROL		
Control	RS232C, IR, Ethernet (10BaseT/100BaseT)	
CONNECTIVITY		
Interfaces frontside	1 x RJ45 (LINK: HDBaseT) 1 x RJ45 (Ethernet) 1 x IR in (3.5 mm jack) 1 x IR out (3.5 mm jack)	1 x RJ45 (LINK: HDBaseT) 1 x RJ45 (Ethernet), HDMI
Interfaces backside	Internal OPS-interface (JAE 80-pin connector)	1 x IR in (3.5 mm jack) 1 x IR out (3.5 mm jack) 1 x RS-232C (9-pin D-sub) Input
ELECTRICAL		
Power Consumption [W]	5 (max.)	4
Voltage / Current [V/A]	16 / 0.33	5 / 2
ENVIRONMENTAL CONDITIONS		
Operating Temperature [°C]	+0 to +40	
Storage Temperature [°C]	-10 to +60	
Operating Humidity [%]	20 to 80	
Storage Humidity [%]	10 to 90	
MECHANICAL		
Net Weight (kg)	0.6	0.5
Gross Weight (kg)	1.0	1.0
Net Dimensions (W x H x D) [mm]	0.20 x 0.03 x 0.12	0.14 x 0.025 x 0.114
Gross Dimensions (W x H x D) [mm]	0.28 x 0.07 x 0.20	0.28 x 0.07 x 0.20
ADDITIONAL FEATURES		
Compatibility	All NEC Large Format Displays with Option Slot (OPS or DualSlot), NEC PX and NEC PH Series Projectors	
Warranty	3 Years Warranty, Additional services available	
Shipping Content	OPS HDBaseT Receiver (SB-07BC), User Manual, External IR sensor	HDBaseT Transmitter (KT-100TX1), User Manual, External IR sensor
Regulatory Approvals	CE, RoHS, VCCI (class B), RCM, FCC	
For additional pictures and Solutions overview, Visit www.nec-display-solutions.com for details.		

This document is © Copyright 2015 NEC Display Solutions Europe GmbH. All rights are reserved in favour of their respective owners. The document, or parts thereof, should not be copied, adapted, redistributed, or otherwise used without the prior written permission of NEC Display Solutions Europe GmbH. This document is provided "as is" without warranty of any kind whatsoever, either express or implied. Errors and omissions are accepted.

NEC Information:
Call: +49 (0)89/99 699-0

www.nec-display-solutions.com

NEC Display Solutions Europe GmbH may make changes, revisions or improvements in, or discontinue the supply of any product described or referenced in this document at any time without notice. 29. January 2015

Empowered by Innovation

